



## NK ALARM AMPLIFIER



Monitors up to 30 sensors with a single output.

### APPLICATIONS

- Create a monitoring system using EM-series multi-tube flow meters
- Lubrication oil monitoring
- Industrial fluid flow monitoring
- Process control

### FEATURES

- Connections for up to 30 sensors
- Alarm indicator LED on front cover
- SPDT potential free contact
- Single output

NK ALARM AMPLIFIER

### SPECIFICATIONS

MODEL	NK ALARM AMPLIFIER
SUPPLY	110 VAC or 220 VAC
Inputs	Inductive proximity sensors
Outputs	10A 250 VAC 10A @ 24 VDC 1/4 HP @ 120 VAC
Protection	IP 54
Local indicators	Green: Power ON Red: ALARM
Build options	Supply voltage, number of inputs
Optional accessories	Connect up to 30 alarm sensors, custom enclosure, stand-alone or interlock operation



NK ALARM AMPLIFIER

## NK2 LOW FLOW ALARM

<b>NK2</b>		-	/	
INPUTS	1 - 2 inputs			2
	1 - 6 inputs			6
	1 - 12 inputs			12
	1 - 20 inputs			20
	1 - 30 inputs			30
SUPPLY VOLTAGE	110 VAC			110
	220 VAC			220



ALARM SENSOR