

SEAL WATER MONITOR EDF

DUAL FLOW MONITOR

1 LPM	17 GPH	120
3 LPM	50 GPH	350
8 LPM	2 GPM	82
13 LPM	3.5 GPM	1335

BODY MATERIAL Delrin® (POM)	P
Kynar® (PVDF)	K

CONNECTION TYPE

3/8" ID hosebarb	H
1/4" NPT/M adapter	M
1/4" NPT/F adapter	N
1/2" OD straight tube	O
1/2" ID hosebarb	R
3/8" OD straight tube	S
3/8" compression fittings (c/w nut & ferrules)	T
10mm hosebarb	W
1/2" compression fittings (c/w nut & ferrules)	Y

PRESSURE 15 psi	A
GAUGE 30 psi	B
60 psi	C
100 psi	D
160 psi	E
200 psi	F
300 psi	G
400 psi	H
100 psi with red set pointer	I
160 psi with red set pointer	J
200 psi with red set pointer	K
300 psi with red set pointer	L
400 psi with red set pointer	M
No pressure gauge	X

PRESSURIZING VALVE, standard on EDF

STAND Floor mounting stand	S
No stand	X

ALARMS Alarm 10-55 VDC 150 mA (IG 5919)	A
Alarm 20-250 VAC/DC 300 mA (IG 0374)	B
Dual Alarm 10-55 VDC 150 mA	C
Dual Alarm 20-250 VAC/DC 300 mA	D
No alarm	X