

SEAL WATER METER

ESF -

SINGLE FLOW MONITOR

1 LPM	20 GPH	120
3 LPM	50 GPH	350
8 LPM	2 GPM	82
13 LPM	3.5 GPM	1335

BODY MATERIAL	Delrin (POM)	P
	Kynar (PVDF)	K

CONNECTION TYPE	
3/8" ID hosebarb	H
1/4" NPT/M adapter	M
1/4" NPT/F adapter	N
1/2" OD straight tube	O
1/2" ID hosebarb	R
3/8" OD straight tube	S
3/8" compression fittings (c/w nut and 2 ferrules)	T
10mm ID hosebarb	W
1/2" compression fittings (c/w nut and 2 ferrules)	Y

PRESSURE	15 psi	A
GAUGE	30 psi	B
	60 psi	C
	100 psi	D
	160 psi	E
	200 psi	F
	300 psi	G
	400 psi	H
	100 psi with red set pointer	I
	160 psi with red set pointer	J
	200 psi with red set pointer	K
	300 psi with red set pointer	L
	400 psi with red set pointer	M

OPTIONS	Pressurizing valve (for double seal)	P
	No pressurizing valve	X

STAND	Floor mounting stand	S
	No stand	X

ALARMS	Alarm 10-55 VDC 150 mA (IG 5919)	A
	Alarm 20-250 VAC/DC 300 mA (IG 0374)	B
	No alarm	X